



# LIFTBOY 1/2/3



#### The vertical platform lift for lifting heights up to 970 mm

Where ramps are too steep or too long – where stairlifts or elevators are needless due to too small a difference in altitude – the Liftboy is the optimal solution. With the help of our Liftboy models, wheelchair users and physically disabled persons can get over differences in altitude of up to 97 cm.

The Liftboy is designed for indoor and outdoor use! As the weatherproof lifting platform with a total weight of only 70 kg can easily be put up, it offers a perfect solution also for urgent or temporary needs. The lift can be equipped with special side entry or exit, upper access gate or transport wheels.

### **LIFTBOY 1/2/3**

#### Simple Installation

The simple construction allows a fast installation with minimal structural works necessary on site.

#### **Comfort**

Optimal drive comfort is ensured by a stable and smooth lifting movement.

#### Reliable

Designed for outdoor or indoor installation, a strong motor in combination with robust electronics ensure a reliable and low-maintenance performance.



Simple placement of unit for temporary uses





**Handset on spiral cable** for a conforable control on the platform







Version with **side exit on upper level** and control pillar



**Platform in a pit** as an option with obstruction-free surface

## **Main advantages** of the Liftboy

- Silent, stable and smooth driving experience
- Simple to transport and fast to install
- Available in any RAL colour
- Available as outdoor version
- Optional with a door for the upper landing or with a safety bar on the platform
- Optional with transport wheels for mobile version
- Optional with extra long access ramp for easy access
- 90° entry-exit is possible

**Optional safety bar** for creating barrier at upper level when platform is down







**Mechanical access ramp** folds down when unit is lifting and creates a barrier against rolling off the platform



Version for public buildings with **door**with electric lock for upper landing and a control pillar

#### Liftboy 1/2/3 - Technical Specification

Facts			Construction examples
Type	Liftboy 1	Liftboy 2 / 3	Standard
Lifting height	595 mm	830 / 970 mm	180° entry-exit
Loading capacity	180 kg	300 / 240 kg	
Lifting speed	15 mm/s	15 mm/s	Side exit on top level
Minimum height of platform	100 mm	120 / 135 mm	
Drive system	24V actuator with scissor mechanism	24V actuator with scissor mechanism	
Internal dimensions	713 × 1170 mm	800 × 1495 mm	Side entry on lower level
External dimension	810 × 1180 mm	924 × 1505 mm	
Power supply	1 × 230V / 50-60Hz	1 × 230V / 50-60Hz	

#### Together we provide accessibility!

For further information please contact:



Platform stairlifts



Chair stairlifts



Vertical platformlifts



Stairclimbers



**Poollifts** 

Official partner of:

